





Manufacturer & Exporters of : LABORATORY TESTING INSTRUMENTS



CE GMP NSIC



An ISO 9001:2008 CERTIFIED An ISO 10002:2004 CERTIFIED



Electronic Balance



- External calibration / Motorized Internal Calibration with built in weight
- •A built in under hook for below weighing
- Easy to read Backlight LCD Display
- •Density measurement for solid & liquid (Optional)
- Standard RS 232 C Interface (Optional)
- •Auto Timing Calibration
- •Percentage (%) Weighing
- •High Resolution, Quick Weighing,
- •Based on E.M.F.C. Technology
- •Tare range upto max. Capacity
- Multiple Weighing Units
- ·Level Indicator, Adjustable fit
- •Counting Weighing mode
- •Units Conversion and data output
- Overload Protection

Electronic Balance

CAPACITY	220 Gms
READABILITY	0.1 mg.
REPEATABILITY (±)	0.1 mg.
LINEARITY	0.2 mg.
PAN SIZE (mm/inch)	90 mm
RESPONSE TIME	3-4 sec.
CALIBRATION	External / Motorized Internal
TARE RANGE	Full
OPERATING TEMP.	15°C to 35°C
POWER SUPPLY	A/C adapter 230 V

NOTE: ELECTRONIC BALANCES IN OTHER CAPACITIES WITH DIFFERENT READABILITY ARE ALSO AVAILABLE ON REQUEST.

E-mail: info@opticstechnology.in, opticstechnology@gmail.com Website: www.opticstechnology.in