

SINCE 1978



OPTICS TECHNOLOGY

Manufacturer & Exporters of : LABORATORY TESTING INSTRUMENTS



An ISO 9001:2008 CERTIFIED
An ISO 10002:2004 CERTIFIED

CE Certified

Refrigerated Humidity Chamber



Double Walled Inner S.S. 304 Outer M.S. Duly Powder Coated / S.S. 304
Gap between the walls is filled with special PUF Insulation.

CFC FREE COMPRESSOR

Temp. & Humidity is controlled by Digital Temp. & Humidity Controller.

Atmospheric conditions are created within the chamber.

Humidity is created in a S.S. Water Reservoir fitted at the back to provide RANGE
FROM Atmospheric humidity upto 95% RH Humidity.

Supplied with S.S. wire mesh trays

Complete with Cord & Plug to work on 220 Volts A.C.

Built in Low water level cutoff device system for the safety of heater

Model :- Refrigerated model

**Temp. From +5°C to 50°C; C ± 1°C, Humidity Amb. atmospheric humidity upto
95% ± 3% RH**

Refrigerated Humidity Chamber

Working size:-

450 x 450 x 700 mm

600 x 600 x 600 mm

600 x 600 x 900 mm

Outer Body of construction :- M.S. duly powder coated body OR Stainless steel S.S. 304 Body

OPTIONAL

Microprocessor based Temp. & Humidity Controller

2/3, DSIDC, Community Works Centre, J-Block, Shakurpur, (Opp. Britannia Ind. Ltd.) Delhi-110034 (India)

Phone: 0091-11-27101383, 27184490, Fax: 0091-11-27108890

E-mail: info@opticstechnology.in, opticstechnology@gmail.com

Website: www.opticstechnology.in